




CORIO CD-200F Refrigerated/Heating Circulator

The new generation of laboratory circulators for routine work and standard tasks

Refrigerated / Heating Circulators of the new CORIO™ series distinguish themselves with a great price-to-performance ratio. They are ideal for all standard tasks and routine work in laboratories and industry.

Your advantages

- Models for internal and external applications
- Bright, white, easy to read display
- Very quiet
- Easy pump change-over (internal and external circulation)
- External pump connections (M16x1)
- USB connection
- Space-saving cooling coil design yields more usable space in the bath tank
- Bath lid and drain tap included
- Removable ventilation grid
- Refrigeration unit without side vents
- Class III (FL) according to DIN 12876-1



- Cool-down time (Ethanol)
- Heat-up time (thermal)
- Pump capacity (Water)

Technical Data

Order No.	9012701								
Model series	CORIO								
Category	Refrigerated - Heating Circulators								
Working temperature range (°C)	-20 ... +150								
Temperature control	PID								
Temperature stability (°C)	±0.03								
Setting / display resolution	0.01 – 0.1 °C								
Temperature Display	LED								
Heating capacity (kW)	2								
Cooling capacity (Medium Ethanol)	<table border="1"> <thead> <tr> <th>°C</th> <th>20</th> <th>0</th> <th>-20</th> </tr> </thead> <tbody> <tr> <td>kW</td> <td>0.22</td> <td>0.17</td> <td>0.06</td> </tr> </tbody> </table>	°C	20	0	-20	kW	0.22	0.17	0.06
°C	20	0	-20						
kW	0.22	0.17	0.06						
Pump capacity flow rate (l/min)	15								
Pump capacity flow pressure (bar)	0.35								

Bath opening / bath depth (W x L / D cm)	13 x 15 / 15
Pump connections	M16x1
Barbed fittings diameter (inner dia. / mm)	8 / 12
Filling volume liters	3 ... 4
Refrigerant stage 1	R134a
Filling volume refrigerant stage 1 (g)	70
Global Warming Potential for R134a	1430
Carbon dioxide equivalent stage 1 (t)	0.1
Ambient temperature	5...40 °C
Dimensions W x L x H (cm)	23 x 39 x 65
Weight (kg)	26
Included with each unit	2 each barbed fitting for tubing 8 and 12 mm inner dia. (pump connections M16x1 male)
Bath tank	Stainless steel
Bath cover	integrated
Cooling of compressor	Air
Available voltage versions	230 V / 50 Hz 208 V - 230 V / 60 Hz 115 V / 60 Hz 100 V / 50-60 Hz

Characteristics



100% Checked.

100% testing. 100% quality. Each CORIO™ undergoes thorough quality testing before leaving the factory.



Quick start.

Individual JULABO consultation and comprehensive manuals at your disposal.



ATC.

Absolute Temperature Calibration, 1-point calibration (CD).



Safety.

CORIO CD complies with Class III (FL) according to DIN 12876-1 and switches off automatically in case of high temperature or low liquid level alarm.



Brilliant.

Bright display with strong illumination can be viewed easily from a long distance.



Satisfied customers.

11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.



Condensation protection.

Superb design solution. Integrated ventilation directs air over the bath lid and minimizes condensation.




Services 24/7.

Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.



Connection. Easy.

Inclined pump connections (M16x1) facilitate the connection of applications. Each unit includes 2 barbed fittings of 8/12 mm diameter each.



Solid.

Minimized energy loss through high-quality insulation.



Everything at the front.

All operating controls and safety functions are accessed easily and comfortably from the front.



Space saving. Free up space.

Place your CORIO right next to an application, another unit, or wall. That saves space. This is made possible by eliminating vents and connections on the sides.



Exact.

You can rely on it. PID1 control and 'Active Cooling Control' make the new CORIO™ precise and perfect.



Stable.

Rubber feet allow for a secured footing of your CORIO™ to prevent damage to your laboratory equipment.



Green technology.

Development consistently applied environmentally friendly materials and technologies.



Switch on. And off you go.

Intelligent operating concept. Ready for operation with just a few quick and easy steps.



Handle with ease.

Makes day-to-day work easy. Comfortably move your CORIO™ around by using the ergonomic handles (front and rear).



Switch on. And off you go.

Intelligent operating concept. Ready for operation with just a few quick and easy steps.



Internal. External.

The pump is controlled via a lever located directly below the display. Easily change between internal and external circulation.



Tidy.

The special drain tap for easy draining of bath fluids without tools.



JULABO. Quality.

Highest standards of quality for a long product life.



Timer. Integrated.

CORIO circulators include an integrated timer function. When the set time has elapsed, a signal sounds and the device switches off. Setting range: 0 ... 999 minutes



Locked in.

The lockable power plug guarantees safe connection. More process safety.



Touching permitted.

Optimum safety. The ergonomic plastic handle protects your fingers from hot surfaces.




Mobile.

Extra easy handling. Integrated castors for easy repositioning of refrigerated circulators. (CD-600F, CD-601F, CD-900F, CD-1000F, CD-1001F)



Unique.

Specially designed pyramids ensure that the condensed liquid drips directly back into the bath.



Modern. Reliable.

High-grade components in every CORIO – platinum sensors, proven motor technology, CAN-Bus communication and much more.



USB.

Remote control made easy. CORIO CD circulators feature a USB connection.